Goodwind

GW-S352D5

SDEC-Diesel Generator Set





Standards : CE: 2006/42/EC Machinery safety, ISO 9001, ISO 14001, ISO 45001, GB/T 2820.5, ISO 8528

Conditions : Reference environmental conditions according to the ISO 8528-1:2018 standard: Atmospheric pressure 100 KPa, ambient temperature 25°C, relative humidity 30%.

PRP: According to ISO 8528-1:2018, prime power refers to the generator set under agreed operating conditions and maintained in accordance with the manufacturer's specifications. The generator set is used in variable load applications and has no running hour limit throughout the year. The average allowable output power for 24 hours of continuous operation shall not exceed 75% of the rated power.

ESP : According to ISO 8528-1:2018, emergency power refers to application when the grid power is outage, or application under test conditions, and the annual running time does not exceed 200 hours. The average allowable output power for 24 hours of continuous operation shall not exceed 75% of the standby rated power.

GENERATOR SPECIFICATION

ITEMS	PRP	ESP
Power	320 kVA	352 kVA
Power	256 kW	282 kW
Frequency/Phase/RPM	50Hz / 3P / 1500	
Standard voltage	400/230V	
Available voltage	380/220V to 415/240V	

Water-cooled | Three Phase | 50 Hz | Diesel

GENERAL INSTALLATION

ITEMS	OPEN	SILENT
Dimension(L*W*H)(mm)	3100*1150*1609	3800:1660:2100
Weight(kg)	3000	4100
Fuel tank(L)	-	600
Sound pressure level		
@75%load @1m db		88
@75%load @7m db		75



NOTE: Weights and dimensions based on standard products. According to 2000/14/CE , sound data is provided at 7m for 75% prime power. For Actual installation,please contact the manufacturer.

PERFORMANCE DATA

Engine brand		SDEC
Fuel		Diesel
Aspiration		Turbo charged
Cooling		Water-cooled
Governor		Electric
Displacement		11.8L
Application		Prime&Standby
Fuel consumption	100%ESP(L/H)	81.6
	100%PRP(L/H)	73.3
	75%PRP (L/H)	53.7
	50%PRP (L/H)	37

Goodwind

GW-S352D5

SDEC-Diesel Generator Set

ENGINE SPECIFICATION

Performance Data

Engine brand	SDEC
Engine model	6ETAA11.8-G33
Engine power	307/338KW
Cylinder arrangement	6 in line
Bore and stroke	128X153mm
Compression ratio	17:1
Rated speed	1500rpm/min
Engine type	4-stroke diesel

Exhaust System

Exhaust gas temperature	600°C
Exhaust gas flow	55.7m^3/min
Max back pressure	10kpa

Fuel system

Injection pump	BOSCH
Governor	Electronic

Cooling system

Cooling method	Fresh water forced circulation
Water pump	Centrifugal type driven by belt
Cooling fan	Blower type, plastic
Prime engine coolant temperature	102/100°C (Max.)

Electrical System

Charging generator	28V*55A
Starting motor	24V*7.5kW
Battery Voltage	24V
Battery Capacity	180AH

Air Intake System

Air Filter	Dry type
Intake flow rate	22.9m^3/min
Max. permissible restrictions	3kPa
Maximum allowable temperature for combustion air to enter	50°C

ALTERNATOR SPECIFICATION

Basic data

Insulation & temperature rise	Class H / H
Excitation type	Self-excited
Winding leads	12
Winding connections (standard)	Star
Winding pitch	Two thirds
Number of phase	Three phase

ALTERNATOR SPECIFICATION

Basic data

Type	Brushless
No.of bearings	Single
Coupling system	Flexible disc
Maximum over speed	2250RPM
Coating type	Vacuum impregnation
IP rating	IP23

Goodwind

GW-S352D5

SDEC-Diesel Generator Set

GENSET VERSION

Standard features
● Diesel engine,50 degrees radiator, brushless alternator
● Intelligent controller
● Output circuit breaker(up to1250A)
● Maintenance-free start battery, battery charge, battery switch
● Steel industrial; silencer, exhaust bellows and elbows
● Steel chasis and anti-vibration shock absorbers
● Lifting and moving structure, expansion of oil and coolant discharge
● Moving parts protection, hot parts protection
● Special toolbox,delivery attached documentation



Optiona	Featuresl
ENGINE	● Water jacket preheater ● Oil Preheater, oil level maintainer,oil manual pump ● Heavy air filtration ● Residential silencer ● Remote radiator, heat exchanger
ALTERNATOR	● PMG/AREP excitation system ● Anti-condensation heater ● Winding/bearing RTD ● Double bearing structure ● IP44 protection class
CONTROL SYSTEM	● Synchronizing panel, remote control panel ● RS232/485,4G & GPS wireless, ethernet communication card ● Additional digital / analog input/output ● Monitoring software, mobile APP ● Ni-Cad batteries
GENERATING SET	● External fuel tank automatic fuel feeding ● ATS/output/combining/distribution cabinet ● Load test cabinet ● Mobile trailer ● Customized design

Ideal for...



Goodwind

GW-S352D5

SDEC-Diesel Generator Set

CONTROL SYSTEM
KEY FEATURES



Single generator set control-ler can be used in prime or standby scenarios

Manual and remote start,MRS application

Auto mains faiure,AMF application

Genset power/frequency/factor/voltage/current detection

Engine/alternator /generator protections/emergency stop

Event log /running hours history / maintenance warning,LCD screen

User access management, software and tools are easy to use

Input or output configuration, USB communication port



+86 19708412781

info@goodwindpower.com

www.goodwindpower.com